

Simple rod «FRANKLIN type » 2 meters

These stainless steel "Franklin type" single rod lightning rods are used for lightning protection.

This model of lightning rod is 2m high and can be increased by extension masts from the FRANKLIN France range.

The "Franklin Type" single rod offers a protection radius in accordance with the protection standard (IEC/NF EN 62305-3) between 5.5m and 19.80m depending on height and level of protection.

It can be fixed by fixings from the FRANKLIN range (tripod, offset legs, cross fixings, etc.)

The models of water deflecting cones can be used if necessary at the base of the point to overcome any problem of sealing when installing through the roof.

Available in 4m height, stainless steel mast (AFA4001PF).

Available in 6m height, stainless steel mast (AFA6001PF).

Available in 8m height, stainless steel mast (AFA8001PF).



Characteristics

Reference :	AFA2001PF
Type of installation :	Lightning rod « Franklin type »
Assembly :	Installation at the highest point of the structure to be protected using FRANKLIN France fixings chosen according to the type of structure & height
Use :	Small structures protection : pylons, chimneys, ...
Display :	-
Contents :	Single rod tip (AFE1200PC) and connecting collar (AFJ3100SE)
Conductors :	-
Material :	304L stainless steel
Dimensions :	2000 x Ø max 20mm
Weight :	5 kg
Index of protection :	-
Standards :	IEC/NFEN 62305-3

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice