

Simple rod «FRANKLIN type » 4 meters

AFE1200PC



These stainless steel "Franklin type" single rod lightning rods are used for lightning protection.

This model of lightning rod is 2m high and can be increased by extension masts from the FRANKLIN France range.

The "Franklin Type" single rod offers a protection radius in accordance with the protection standard (IEC/NF EN 62305-3) between 5.5m and 19.80m depending on height and level of protection.

It can be fixed by fixings from the FRANKLIN range (tripod, offset legs, cross fixings, etc.)

The models of water deflecting cones can be used, if necessary, at the base of the point to overcome any problem of sealing when installing through the roof.

Available in 2m height, stainless steel mast (AFA2001PF).

Available in 4m height, stainless steel mast (AFA4001PF).

Available in 8m height, stainless steel mast (AFA8001PF).



AFH1051CS



AFJ3100SE

Characteristics

Reference :	AFA6001PF
Type of installation :	Lightning rod « Franklin type »
Installation:	Installation at the highest point of the structure to be protected using FRANKLIN France fixings chosen according to the type of structure & height
Use :	Small structures protection : pylons, chimneys, ...
Display :	-
Contents :	Single rod tip 2m (AFE1200PC), sleeve 16/34 (AFE1634MP), stainless steel collar (AFH1051CS), connecting collar (AFJ3100SE), threaded mast \varnothing 34 (AFZ4015MR), fitting \varnothing 34 for mast \varnothing 34 (AFC3434MR), stainless steel mast 33.7x3.2 LG (AFZ0034MR)
Conductors :	-
Material :	Acier inoxydable 304 L
Dimensions :	6000 x \varnothing 35 mm
Weight :	16,5 kg
Index of protection :	-
Standards :	IEC/NFEN 62305-3

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice