



Stainless Steel Extension Mast Lightning rod elevation

Stainless Steel Extension Mast Active 2D/4D



Made of stainless steel, the extension masts allow a lightning conductor to be raised up to 6 m without guying.

The various components are assembled together by fitting them together

The end of the **AFC2242MR** mast is equipped with a fitting system to receive the Active 2D/4D Early Streamer Emission (ESE) without additional accessories.

The **AFC2442MR** mast kit (including 2 masts) allows to reach a height of 4 meters.

The **AFC2642MR** mast kit (including 3 masts) allows to reach a height of 6 meters.

Details masts 1 ϕ 42 with fitting 34/42



Details mast 2 With fitting 42/42



Details mast 3 With fitting 42/42



Characteristics :

Reference :	AFC2242MR	AFC2442MR	AFC2642MR
Designation :	Stainless steel mast 2m 2D	Set of stainless steel masts 4m 2D	Set of stainless steel masts 6m 2D
Length (m) :	2,00	4,00	6,00
Outer diameter (mm) :	34 - 42	42	42
Weight (kg) :	8,2	16,7	25,2
Material :	304L stainless steel		
Extremity :	With fitting 34 / 42	With fitting ϕ 42	

Franklin Technologie[®] - Une gamme complète de protections contre la foudre et les surtensions
Dans le cadre du développement continu de ses produits, Franklin France se réserve le droit d'en modifier les spécifications sans préavis.