

Guying Kit



The guying kit makes it possible to maintain all the lightning conductors and extension masts of the FRANKLIN France range as well as the pylons in metal lattice beams according to the type of installation desired and the wind region. It is made up of a 50 m Ø 5.6 mm fiberglass crown, 3 turnbuckles, 6 anchor clamps, a 3-way guying collar, 3 Ø6 mm stainless steel shackles and a set of 3 expansion plugs Ø10mm.

This kit can be completed with the following accessories:

- Fiberglass Anchor Clamp (AFD1051KU)
- Turnbuckle 1 eye, 1 clevis Ø 12 mm (AFD1052KU)
- 3 Way Guy Collar (AFD1055KU)
- Double expansion dowel Ø 12 mm (AFD1062KU)
- Stainless steel shackle Ø 6 mm (AFD1070KU)

Characteristics

Reference :	AFD1050KH
Type of installation :	Lightning rod
Assembly :	<p>Assembly of the lightning conductor and its masts on the ground and/or the pylon, installation of the 3-way guying collar, cutting of the 3 stay cables and installation at the level of the collar.</p> <p>Installation of anchor points and central support. Straightening of the lightning rod and/or pylon, connection of each stay, adjustment of plumb and final tightening.</p>
Use :	Maintenance of lightning rod and/or pylon according to wind region.
Display :	-
Contents :	-
Material :	Fiberglass – galvanized steel – stainless steel
Dimensions :	-
Weight :	< 10 kg
Index of protection :	-

Franklin Technologie® - A full range of lightning and overvoltage protection.
 In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice