

1 mètre strike point



The strike point is used in the placement of mesh cage type protection. Its usefulness must be validated by the method of angles or the fictitious sphere.

It can be combined with the following products:

- Connection bracket (AFF0501PC) and (AFF0502PC)
- Platinum support (AFF0835PC)
- Point support pedestal (AFF8036PC)
- Bracket bracket (AFF0836PC)
- Threaded Rod (AFF2025PC)
- Tip support base (AFF0503PC)

Platinum support,
AFF0835PC + AFF0501PC



Point support stud
AFF8036PC + AFF0501PC



Angle support
AFF0836PC + AFF0501PC



Threaded shaft
AFF2025PC + AFF0501PC



Tip support base
AFF0503PC + AFE1050PC



Caracteristics

Reference :	AFE1100PC
Type of installation :	Meshed cage
Assembly :	To be screwed and interconnected with one of the mesh conductors, depending on the connection system chosen.
Use :	Additional meshed cage installation
Display :	-
Conductor :	-
Material :	Stainless steel
Dimensions :	1000 x Ø 20mm and internal thread M10
Weight :	2,178 kg
Clamping diameter :	-
Standards :	NF EN 62561-2

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice