

Lightning products Meshed Cages

1 meter strike points

*in compliance with **NF EN 50164-1** standard*



Strike point is used to install a protection type meshed cage.
Their utility should be validated by the angles method or fictive sphere.

It can be associated to the following products:

- Extra fixing bracket ref AFF0501PC and AFF0502PC
- Support plate, ref AFF0835PC
- Cement «support point», ref AFF8036PC
- Support angle, ref AFF0836PC
- Threaded rod, ref AFF2025PC
- « point support » base, ref AFF0503PC



Support plate,
ref AFF0835PC
+ AFF0501PC

Cement « support point»
stud, ref AFF8036PC +
AFF0501PC

Support angle, ref
AFF0836PC +
AFF0501PC

Threaded rod ref
AFF2025PC +
AFF0501PC

«support Point»
base, ref
AFF0503PC +
AFE1050PC



CHARACTERISTICS

| | |
|------------------------|--|
| Reference : | AFE 1100 PC |
| Type of installation : | Meshed Cage |
| Assembly : | To screw and to interconnect with one of the meshing conductors according to the chosen connection system. |
| Use : | Meshed cage installation additional |
| Display : | - |
| Conductors | - |
| Material : | Stainless steel |
| Dimensions : | 1000 x Ø 20mm and internal thread M10 |
| Weight : | 2,178 kg |
| Protection index : | - |
| Standards : | NF EN 50164-1 |
| | |
| | |

Last update : 09/12/2014

Franklin Technologie © - A full range of lighting and overvoltage protection.
In the continue framework of its products, **Franklin France** shall be entitled to modify specifications without notice