

Extra fixing bracket for tape



This bracket allows interconnecting conductors like meshing tape or down conductor to meshed cage strike point.

Interconnection with 27x2mm tin-plated tape, 30x2mm stainless steel tape, 30x3mm aluminum tape, 33,5x3mm galvanized steel conductors shall work by strike point fitting.

Piece drilled at Ø 11mm allowing a connection with M10 screw.

It can be combined with the following products:

Support plate
(AFF0835PC)



Cement support point
stud (AFF8036PC)



Support angle
(AFF0836PC)



Tige filetée
(AFF2025PC)



Also for round conductor Ø8 and 10 mm (AFF0502PC)

Characteristics

Reference :	AFF 0501 PC
Type of installation :	Meshed Cages
Assembly :	Putting this bracket around the conductor, the pressuring works by strike point fixing
Use :	Conductor and single rod interconnection
Display :	-
Contents :	Strip section 27x2 mm to 33.5x3 mm
Material :	Tin-plated copper
Dimensions :	64 x 28 x 10 mm
Weight :	0,070 kg
Index of protection :	-
Standards:	NF EN 62561-1

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice