

25x3mm tinned copper tape

in compliance with NF EN 62561-2 standard



Available in bare copper, ref AFG0254CP



This conductor is designed for flowing the lightning current and equipotential connections realization.

Its use will be favor for the installation of the capture conductors, down conductors, and lightning earthing network type A and/or B.

This conductor can be maintained by all the fixings of FRANKLIN France range such as AFH6414AC, AFH6415AC, AFH6416AC, AFH6500CL, AFH8039PC, AFH2030CM, AFH7000AC, AFH2001AC, and AFH6032BM

Equipotential connections can be done with silver brazing, welding, or clamping mechanical pieces of FRANKLIN France range type flat/round coupling ref AFJ0819RL, cross coupling AFJ0005RC.

The space between each fixing will be determined according to the applicable installation standard.

Characteristics

Reference :	AFG 0253 CP
Type of installation :	Down conductor, meshed cage, ground network
Assembly :	Fixing by fitting or pressuring according to chosen fixing and installation standard.
Use :	Distributing and/or lightning current capture
Display :	-
Conductors :	75mm ² section tape
Material :	Tin-plated copper
Dimensions :	25 x 3 mm
Weight :	0,670 kg/m
Indice de protection :	-
Standards :	EN 13601-2002 – NF EN 50164-2 – NF EN 62305-3

Franklin Technologie® - A full range of lighting and overvoltage protection.
In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice