

### Stainless steel strapping 30 x 2 mm (by 50 m)



This conductor is used for the flow of the lightning current and the creation of equipotential bonds. Its use will be favored for the realization of capture conductors, down conductors and type A and/or B lightning earth network.

This conductor can be held by all the fasteners in the FRANKLIN France range including the AFH6414AC, AFH6415AC, AFH6416AC, AFH6500CL, AFH8039PC, AFH2030CM, AFH7000AC, AFH2001AC, AFH6032BM fasteners.

The choice of fixing and the distance between the conductor and the support will depend on the rise in temperature of the conductor according to the level of protection.

The equipotential links can be connected to the down conductors and capture conductors by aluminothermic welding or mechanical clamping parts from the FRANKLIN France range of the flat/round connector type (AFJ0819RL), crossing connector (AFJ0005RC).

The spacing between each fixing will be determined according to the applicable installation standard (NFC 17102 or NF EN 62305-3).

Available in roll of 25m (AFG1011CP).

### Caracteristics

Reference :	<b>AFG1012CP</b>
Type of installation :	Down conductor, meshed cage, earth network
Use :	Fixing by clamping or pressurizing depending on the fixing chosen and the installation standard.
Reference :	Flow and/or capture of lightning current
Display :	-
Conductor :	Section strip 60mm <sup>2</sup>
Material :	Stainless steel
Dimensions :	30 x 2 mm
Weight :	0,480 kg/m
Index of protection :	-
Standards :	NF EN 62561-2

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice