

Galvanized steel strapping 33,5 x 3 mm



This conductor is used for the flow of the lightning current and the creation of equipotential bonds.

Its use will be favored for the realization of capture conductors, down conductors, equipotential links and type A and/or B lightning earth network.

This conductor can be held by all the fasteners in the FRANKLIN France range, including the AFH6503CL, AFH2030CM fasteners.

The equipotential links can be connected to the down conductors and capture by aluminothermic welding or mechanical clamping parts from the FRANKLIN France range of the crossing connector type (AFJ0005RC).

The spacing between each fastener will be determined according to the applicable installation standard (NFC 17102 ou NF EN 62305-3).

Characteristics

Reference :	AFG2333CP
Type of installation :	Down conductor, meshed cage, equipotential bonds, earth network
Use :	Fixing by clamping or pressurizing depending on the fixing chosen and the installation standard.
Reference :	Flow and/or capture of lightning current
Display :	-
Conductor :	Section strip 100,5mm ²
Material :	Galvanized steel
Dimensions :	33,5 x 3 mm
Weight :	0,810 kg/m
Index of protection :	-
Standards :	NF EN 62561-2

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice