

Frame fixing



Supplied with 4 stainless steel screws $\varnothing 6\text{mm}$

These fasteners are used to fix flat conductors to metal supports such as angle iron, pylon or metal framework.

They can also be used to make equipotential connections between metallic masses.

The conductors of the 27x2mm tinned copper strip, 30x2mm stainless steel strip, 30x3mm aluminum strip and 33.5x3mm galvanized steel strip type conductors are kept under pressure at the upper part of this part.

The upper part can be rotated 360°.

The spacing between each fixing will be determined according to the applicable installation standard (NFC 17102 or NF EN 62305-3).

Characteristics

Reference :	AFH2001AC
Type of installation :	Down conductor
Assembly :	Base to be screwed onto a metal structure with a maximum thickness of 10mm. Removable top cover with 2 $\varnothing 6\text{mm}$ stainless steel screws
Use :	Fixing of the down conductor and equipotential connections
Display :	-
Conductors	Strip section 27x2mm to 33.5x3mm
Material :	Galvanized steel
Dimensions :	52 x 30 x 37 mm
Weight :	0,105 kg
Indice of protection :	-
Standards :	NF EN 62561-4

Franklin Technologie® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice