

Lightning Products

Conductors fixings

Fixing collar for flat conductor

*in compliance with **NF EN 50164-4** standard*



Delivered with 1 wood screw
M7x40mm

These collars are used to fix flat conductors on all type of support, especially concrete and wood supports.

Conductors type tinned copper strip coil 27x2mm, inox 30x2mm, aluminium 30x3mm, galvanized steel 33,5x3mm are maintained in pressure at the removable superior part.

This product allows spacing the conductor of 10mm regarding to the support (height between the base and the conductor axis).

The main body is M7 threaded

The distance between each fixing will be determined according to the applicable installation standard (NFC 17102 or NF EN 62305-3).

CHARACTERISTICS

Reference :	AFH 7000 AC
Type of installation :	Down conductors can be mutualized
Assembly :	Fixing on all type of support with M7 maxi screw. Removable superior part with 2 inox Ø5mm screws
Use :	Fixing of the down conductor and equipotential connections
Display :	-
Conductors	Strip coil section 27x2 to 33,5x3 mm
Material :	Brass
Dimensions :	50 x 16 x 8 mm (ht 46 mm delivered with screw)
Weight :	0,026 g
Indice of protection :	-
Standards :	NF EN 50164-4

Last update : 09/12/2014

Franklin Technologie © - A full range of lighting and overvoltage protection.
In the continue framework of its products, **Franklin France** shall be entitled to modify specifications without notice