



# Lightning products

## Earth Ground Tester

### Earth Ground Tester



#### Characteristics

Reference :	AFM2408TL
Measurement range :	Resistance : 0 - 20 kΩ Voltage : 0 - 200 V~
Resolution	Resistance : 0.01 Ω Voltage : 0.1 V
Precision :	Resistance : ± 2 % of the measured value ± digits Voltage : ± 2 % of the measured value ± digits
Fréquence d'opération de mesure :	1470 Hz
Operating temperature :	-10 °C to +50 °C
Storage temperature :	-25 °C to +70 °C
Humidity range :	95% RH (non condensing)
Weight :	≈ 1.5 kg
Dimensions :	221 x 189 x 99 mm
Battery :	NiMH Rechargeable Battery AC Adapter 12 V – 1 A
Output current :	Limited to less than 10 mA (max.)
Output power :	Less than 0.5 W

Franklin Technologie ® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice



**Included accessories :**

- 4 steel spikes
- AC Adapter
- Reel with 40 m, red cable
- Reel with 20 m, blue cable
- Reel with 20 m, green cable
- 5 m short black cable
- 5 m short green cable for connection to the ground to be measured
- Connection wire to supply the charger with a 12 V external battery (the car battery)
- Quick reference
- Bag to transport the equipment
- Bag to transport accessories

**Optional accessories :**

- Steel spike
- 2 m cable for interconnection of the additional spikes

FRANKLIN  
FRANCE

Franklin Technologie ® - A full range of lightning and overvoltage protection.

In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice

**FRANKLIN FRANCE**

FT156EN.QLF.00