

Lightning products

Support masts and fixings

SL bracket

*in compliance with **NF EN 50164-1** standard*



Delivered with 2 A2 10x60 and 2 A2 10x140 stainless steel screws, 4 A2 H10 stainless steel nuts and 8 A2 M10 stainless steel plate washers

SL brackets are used to fix, all early streamer emissions and simple rods of FRANKLIN France range equipped with elevation rod or not on vertical framework of tower, metallic framework, so on

This model is used for offset installation of 280 mm with the structure to protect and can be installed on bigger metallic structure (diameter until 110 mm).

Number of binding brackets shall depend on protection height required.

- 1 lightning rod : 2 binding brackets
- 1 lightning rod with 1 elevation rod: 2 binding brackets *
- 1 lightning rod with 2 elevation rods: 3 binding brackets *
- 1 lightning rod with 3 elevation rods: 3 binding brackets *

* Quantity shall be valid according to installation area and weather conditions.

Exists also with a tightening diameter from 30 to 50mm, ref AFZ0512SL

CHARACTERISTICS

Reference :	AFZ 0513 SL
Type of installation :	Fixing of the lightning rod
Assembly :	Clamping of each bracket on the metallic structure, installation of the lightning rod and its elevation rods with the same way.
Use :	To fix and raise a lightning rod to increase its radius of protection
Display :	-
Conductors :	-
Material :	Galvanized steel
Dimensions :	470 mm x 40 mm
Weight :	2,270kg
Indice of protection :	-
Standards :	NF EN 50164-1
Tightening diameter :	30 to 114 mm

Last update : 09/12/2014

Franklin Technologie © - A full range of lighting and overvoltage protection.

In the continue framework of its products, **Franklin France** shall be entitled to modify specifications without notice