

Ridge hook



Supplied with 1 M6 stainless steel screw

These clips are used to fix flat or round conductors to building ridges.

The 27x2mm copper strip, 30x3mm aluminum, 30x2mm stainless steel, 33.5x3mm galvanized steel and Ø8 and 10mm round conductors will be held on this part using the AFH6414AC, AFH6406AC fasteners.



Adjustment of the width of the ridge by sliding, ½ circle adjustable from 170 to 240mm.

The spacing between each fixing will be determined according to the applicable installation standard (NFC 17102 or NF EN 62305-3).

Caracteristics

Reference :	AFH6422AF
Type of installation :	Down conductor
Assembly :	Fixing by tightening using a slider on ridge tiles, supplied with M6 stainless steel screws for adaptation of PVC fasteners AFH6414AC, AFH6406AC
Use :	Fixing down conductor and equipotential bonds
Display :	-
Compositions :	-
Conductors :	Strip section 27x2 to 33.5x3 mm and round Ø8 to 10mm
Material :	Galvanized steel
Dimensions :	140 x 200 x 25 mm
Weight :	0,074 kg
Indice of protection :	-
Standards :	NF EN 62561-4

Franklin Technologie® - A full range of lightning and overvoltage protection.
In the continue framework of its products, Franklin France shall be entitled to modify specifications without notice